

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

	REVISIONS .							
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED			
1		released for production.	7/29/2016	DPD	JAG			
2	17-0007	-3 ADDED HEAT TREAT RC 28-34.	1/18/2017	DPD	JAG			





NOTES:

1. REF. AIRBUS T/N: M653V3005124. 2. PART OF KIT RBEM653V3005101.

DWG NO.

LOCK WASHER EXCHANGE


RBEM653V3005124 MAT'L UNLESS OTHERWISE SPECIFIED


SURFACES = 125/ SPEC 1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 RAWN BY: DUERFELDT IECKED: CLOUGH PS APPR: ANDERSON APPR: LINDSAY USED ON MODEL PROVED: GILBERT H175 CALE 1:2 5/12/2016 SHEET 1 OF 3


4 CCV	V224			UNIT					DRA
ASSY QTY	ASSY QTY	B/O	Part #	QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS PG	;. c	CHE
									OPP
			-1	1	PLATE	1018/1020 CR	2	C	QA A
			-3	3	SHOULDER THUMB SCREW	4140/4142	3	4	APPI
		B/O	-5	1	BAR HANDLE SCREW W/ FOOT	STEEL	M8 X 75mm (CARR-LANE #CLM-875-BHSB) 1		SC

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

	REVISIONS							
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED			







(-1) PLATE DAR AEROSPACE


LOCK WASHER EXCHANGE


DWG NO.	RBEM653V3005124-1				
MAT'L 1018	1020 CR	UNLESS OTHERWISE SPECIF DIMENSIONS ARE IN INCHE			
HEAT TREAT		.XXX ± .005 FRACTIONS ± 1/8	.5		
FINISH ZINC	PLATE	.XX ± .01 ANGLES ±.5° .X ± .1 SURFACES = 1:	25/		
SPEC ASTN	I B633 TYPE I SC 2	1. BREAK ALL SHARP EDGES	V		
DDAMNI DV.	DUEDELLOT	015 x 45° OR 015R			

	LAIL		.X ± .1 SURFACES = 125/				
SPEC ASTM	B633 TYPE I SO	C 2	1. BREAK ALL SHARP EDGES				
DRAWN BY:	DUERFELDT		.015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY				
CHECKED:	CLOUGH		AFTER PLA	ATING			
OPPS APPR:	ANDERSON		3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009				
QA APPR:	LINDSAY		USED ON MODEL				
APPROVED:	GILBERT		H175				
SCALE	1:1 DA	TE 5/1	12/2016	SHEET 2 OF 3			

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

	revisions							
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED			
2	17-0007	-3 ADDED HEAT TREAT RC 28-34.	1/18/2017	DPD	JAG			







SPEC ASTM B633 TYPE I SC 2

2:1

DUERFELDT

ANDERSON

CLOUGH

LINDSAY

GILBERT

DRAWN BY:

CHECKED:

QA APPR:

SCALE

OPPS APPR:

APPROVED:

5/12/2016

DWG NO. RBEM653V3005124-3 MAT'L 4140/4142 UNLESS OTHERWISE SPECIFIED HEAT RC 28-34
TREAT RC 28-34
FINISH ZINC PLATE

DIMENSIONS ARE IN INCHES

.XXX ± .005 FRACTIONS ± 1/8

.XX + .01 ANGLES ± .5°

.X ± .1 SURFACES = 125/ 1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 USED ON MODEL H175

SHEET 3 OF 3

SHOULDER THUMB SCREW